

MAXITRAK TRAKTÖR YAĞI 15W-40

Multigrade Tractor Oil

Description

High quality diesel engine oil developed specifically for turbo diesel engines of tractors and combine harvesters.

Applications

Used for turbo diesel engines of agricultural machines including the latest models.

Benefits

- Cleans the engine by preventing deposits with the help of detergent-dispersant additives.
- Helps preventing oil consumption and wear.
- Extends oil change intervals.
- Reduces product range in the filo by its wide application area.
- Helps engine to start easily in cold conditions, provides effective lubrication in hot conditions.
- Creates high film layer at high temperatures with its high Viscosity Index modifiers.

Performance

API CF-4/CF

Typical Specifications*

SAE Viscosity Grade		15W-40
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,890
Flash Point, COC, °C	ASTM D-92	240
Viscosity, 40 °C, mm ² /s	ASTM D-445	92
Viscosity, 100 °C, mm ² /s		13,7
Viscosity Index	ASTM D-2270	150
T.B.N., mgKOH/gr	ASTM D-2896	10,5
Pour Point, °C	ASTM D- 97	-30
Sulphated Ash, wt%	ASTM D-874	1,2

* Values shown may differ between productions.

