

# MAXITRAK TRAKTÖR YAĞI 20W-50

Multigrade Tractor Oil

## Description

High quality diesel engine oil developed specifically for turbo diesel engines of tractors and combine harvesters.

## Applications

Used for turbo diesel engines of agricultural machines including the latest models.

## Benefits

- Cleans the engine by preventing deposits with the help of detergent-dispersant additives.
- Helps preventing oil consumption and wear.
- Extends oil change intervals.
- Reduces product range in the filo by its wide application area.
- Helps engine to start easily in cold conditions, provides effective lubrication in hot conditions.
- Creates high film layer at high temperatures with its high Viscosity Index modifiers.

## Performance

API CF-4/CF

## Typical Specifications\*

SAE Viscosity Grade		20W-50
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,890
Flash Point, COC, °C	ASTM D-92	260
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	167
Viscosity, 100 °C, mm <sup>2</sup> /s		20
Viscosity Index	ASTM D-2270	136
T.B.N., mgKOH/gr	ASTM D-2896	10,5
Pour Point, °C	ASTM D- 97	-18
Sulphated Ash, wt%	ASTM D-874	1,2

\* Values shown may differ between productions.

