

MAXIMUS TURBO DIESEL EXTRA 15W-40

Heavy Duty Diesel Engine Oil

Description

Long life diesel engine oil, equivalent to super high performance diesel (SHPD) engine oil providing excellent performance in diesel engines operating with low and high sulfur fuels.

Applications

It is recommended for all heavy-duty vehicles, buses, trucks, construction equipment, and generators having diesel engines, especially turbocharged and low-emission diesel engines.

Benefits

- Prevents the engine using fuel with high sulfur content by its high TBN value.
- Reduces wear at high speeds and temperatures.
- Increases combustion efficiency by keeping engine clean.
- Extends spare parts life.

Performance

API CI-4, ACEA E7-16, MB-Approval 228.3, JASO DH-1, GLOBAL DHD-1, MTU Type 2, Volvo VDS-3 RENAULT RV-I/RLD-2, MACK E0-N, CUMMINS CES 20077/78, DETROIT DIESEL DDC 93K215, DEUTZ DQC-III, MAN M3275, CAT ECF-1a

Typical Specifications*

| SAE Viscosity Grade | | 15W-40 |
|--------------------------|-------------|--------|
| Density, @ 15 °C, kg/m³ | ASTM D-4052 | 0,886 |
| Flash Point, COC, °C | ASTM D-92 | 240 |
| Viscosity, 40 °C, mm²/s | ASTM D-445 | 114 |
| Viscosity, 100 °C, mm²/s | | 15 |
| Viscosity Index | ASTM D-2270 | 139 |
| Pour Point, °C | ASTM D- 97 | -30 |

* Values shown may differ between productions.

