MAXIGEAR EP-X 80W-90

High Quality Automotive Gear Oil

Description

Maxigear EP-X 80W-90, is a universal automotive gear oil that is developed for transmission sytems and differentials of passenger cars and heavy duty vehicles.

Applications

Maxigear EP-X 80W-90 is developed for all vehicles operating under all types of workloads. It is used in the gear systems of all passenger cars and heavy duty vehicles that need API GL-4/5 performance level.

Benefits

- Protects the transmission system against wear, by providing the required lubricant film even at low temperatures.
- Prevents rust and corrosion.
- Prevents deposit accumulation at high temperatures, and extends the life of the lubricant due to perfect thermal stability.
- Elongates service life of system components vulnerable to rusting and corrosion.
- Very good aging resistance provides a long life between oil changes.
- Perfect temperature-viscosity compatibility ensured with the smart oil technology.
- Reduces wear at initial operation and provides fuel savings.
- It protects the gear systems against wear by isolating them from water.

Performance

API GL-5, MT-1, MIL-L-2105D, MB 235.0, MAN 342 Type M2, ZF TE-ML 05A/12E/16B/17B/19B/21A

Typical Specifications*

SAE Viscosity Grade		80W-90
Density, @ 15 °C, kg/m³	ASTM D-4052	0,900
Flash Point, COC, °C	ASTM D-92	220
Viscosity, 40 °C, mm²/s	ASTM D-445	142
Viscosity, 100 °C, mm²/s		15,5
Viscosity Index	ASTM D-2270	101
Pour Point, °C	ASTM D- 97	-24

* Values shown may differ between productions.

