

Maximus Turbo Diesel S 15W-40

Heavy Duty Diesel Engine Oil

Description

High quality diesel engine oil ensuring high performance in all diesel engines operating under severe conditions by its superior protection and long life characteristics.

Applications

Recommended for trucks, buses, construction machines, agricultural machines and generators with diesel engine, especially with turbocharged engine.

Benefits

- Provides excellent performance for highway and construction use.
- Reduces pressure drop and evaporation loss.
- Prevents excess wear at cold start.
- Enables excellent results when used with fuels containing high level of sulfur.
- Keeps the engine clean and reduces friction.

Performance

API CF-4/CF/SH, ACEA E2, MIL-L 2104 E

Typical Specifications*

SAE Viscosity Grade		15W-40
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,884
Flash Point, COC, °C	ASTM D-92	240
Viscosity, 40 °C, mm ² /s	ASTM D-445	111
Viscosity, 100 °C, mm ² /s		15,3
Viscosity Index	ASTM D-2270	145
T.B.N., mgKOH/gr	ASTM D-2896	12
Pour Point, °C	ASTM D- 97	-30
Sulphated Ash, wt%	ASTM D-874	1,4

* Values shown may differ between productions.