

Maximus Super Diesel 20W-50

Heavy Duty Diesel Engine Oil

Description

High quality heavy duty diesel engine oil providing high performance for all diesel engine types operating under severe conditions.

Applications

Recommended for commercial vehicles, trucks, buses, construction machines, and generators having diesel engine including turbocharged and supercharged diesel engines.

Benefits

- Prevents pressure drop, evaporation loss and foaming.
- Provides easier cold start and effective protection at high temperature.
- Reduces maintenance costs for long-haul vehicles.
- Decreases product complexity by its wide range of usage.
- Extends oil change intervals.

Performance

API CF-4/CF/SG, VW 505.00, CAT TO-2, Allison C3, MIL-L-2104 D

Typical Specifications*

SAE Viscosity Grade		20W-50
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,892
Flash Point, COC, °C	ASTM D-92	240
Viscosity, 40 °C, mm ² /s	ASTM D-445	176
Viscosity, 100 °C, mm ² /s		19,7
Viscosity Index	ASTM D-2270	128
T.B.N., mgKOH/gr	ASTM D-2896	11
Pour Point, °C	ASTM D- 97	-24
Sulphated Ash, wt%	ASTM D-874	1,2

* Values shown may differ between productions.