

SUPERŞARJ SERIES

Monograde High Quality Diesel Engine Oils

Description

Mono grade high viscosity index engine oil produced with high quality base oils and additives.

Applications

Can be used in heavy duty vehicles.

Benefits

- Thanks to a high level of TBN, protects the engine against rust, corrosion and wear when using high sulphur content fuel.
- Minimizes the deposit under severe conditions, prevents friction.
- Keeps fluidity at low temperatures due to its high viscosity index.
- Increases combustion efficiency by keeping the engine clean.

Performance

API CF/CF-4/SG, MIL-L-2104D ALLISON C3, CAT TO-2

Typical Specifications*

SAE Viscosity Grade		10W	30	30 (20 TBN)	40	50
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,886	0,890	0,902	0,900	0,899
Flash Point, COC, °C	ASTM D-92	220	240	260	260	270
Viscosity, 40 °C, mm ² /s	ASTM D-445	39,8	81	94	125	223
Viscosity, 100 °C, mm ² /s		6	9,8	11	13	19,5
Viscosity Index	ASTM D-2270	107	100	102	98	99
T.B.N., mgKOH/gr	ASTM D-2896	11	11	21	11	11
Pour Point, °C	ASTM D- 97	-30	-18	-18	-15	-12
Sulphated Ash, wt%	ASTM D-874	1,3	1,3	2,4	1,3	1,3

* Values shown may differ between productions.

