

# MAXITRAK TMS OIL 500

## High Performance Transmission and Hydraulic Oil

### Description

Specially developed high performance transmission and hydraulic oil. Reduce clutch vibration and provides superior performance at low temperatures.

### Applications

Used in hydraulics, transmissions and wet brakes of agricultural, construction and industrial vehicles. Meets the specifications of OEM manufacturers which recommend STOU and UTTO type lubricants.

### Benefits

- Provides quiet operation in break systems, due to high performance additives to prevent friction.
- Extremely resistant against wear, oxidation and foaming.
- Ensures smooth power transmission.
- Prevents wear and break downs in transmissions, due to the new additive technology.
- Perfectly compatible with leak tightness elements and standard seal materials.
- Extends the equipment life and reduces maintenance costs.

### Performance

API GL-4, ZF TE-ML 03E/05F/06K/17E/21F, AGCO Massey-Ferguson M1135/ M1141, CNH Case/ New Holland MAT 3525, FNHA-2-C-201, John Deere JDM J20C and J20D, Volvo CE WB-101, ZF TE-ML 03F, AGCO-Allis Power Fluid 821XL, Allis-Chalmers Power Fluid 821, Deutz-Allis 272843, 257541, 246634, Massey-Ferguson M-1110, M-1127A, and M-1127B, M-1129A, M-1135 (Current Worldwide), M-1141 (Current EP THF) M-1143 (Finished Oil) M-1145 (Finished Oil), White Farm Equipment Q-1826 (Current), Minneapolis-Moline Q-1766, Q-1722, Q-1766Bx, Oliver Q-1705, New Idea Q-1802 , Type 55, Allison C-2, C-3 and C-4, Caterpillar TO-2, Case International: MS-1204, 1205, 1206, 1207 ,Case-IH MS-1210, JIC 145 JI Case JIC 143 / 144, International Farmall MS-1204, JIC 185 ,International Harvester B-5, B-6 (International Harvester), Steiger SEMS 17001 (Steiger), New Holland (Fiat): FNHA-2-C-200, Ford and New Holland FNHA-2-C-200A, FNHA-2-C-201, MAT 3225 / Nexplore fluid, 3525, 3526 (Current), ESNM2C41- B, ESN-M2C43, ESN-M2C48-A and ESN-M2C48-B, ESN-M2C53-A and ESN-M2C53- B, ESN M2C92-A, ESN-M2C134-A, B, C, D (Current) ,Sperry-Vickers 35VQ25 and M-2952-S (Vickers), I-286-S (Vickers), M-2950-S (Vickers) ,Versatile Specification 23M or 24M (Versatile), Hesston-Fiat: (tractors only) AF-87, Multi-F, Multi G 134/NH410B (FNHA-2-C-201), Multi-G (Current), John Deere: JDM J20A and J20B JDM J20C and J20D JDM J14B and J14C JDM J21A JDT 303 Quatrol, Komatsu Dresser: B-06-0001 and B-06-0002, Kubota: UDT (Current), Renk Doromat: 873 874 A and 874 B (current), ZF TE-ML 05E

### Typical Specifications\*

SAE Viscosity Grade		10W-30
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,890
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D-445	62
Viscosity, 100 °C, mm <sup>2</sup> /s		9,7
Viscosity Index	ASTM D-2270	140
Pour Point, °C	ASTM D- 97	-33

\* Values shown may differ between productions.

